

GREASE INTERCEPTOR CLEANING LOG INSTRUCTIONS:

1. FILL OUT TOP OF FORM WITH APPROPRIATE INFORMATION
2. ENTER DATE THAT YOU EITHER INSPECT OR CLEAN GREASE INTERCEPTOR
3. ENTER % DEPTH OF GREASE AND SOLIDS THAT YOU MEASURE OR GREASE HAULER MEASURES
4. ENTER NAME OF COMPANY PERFORMING THE CLEANING OF GREASE INTERCEPTOR
5. ENTER CONDITION OF GREASE INTERCEPTOR EITHER DURING YOUR INSPECTION AND/OR AFTER INTERCEPTOR HAS BEEN EMPTIED AND CLEANED
6. ENSURE ALL CONTENTS OF GREASE INTERCEPTOR ARE REMOVED
7. SIGNATURE OF AUTHORIZED PERSON PRESENT DURING ABOVE ACTIONS
8. NOTE COMMENTS (IF ANY) ABOUT ABOVE ACTIONS (USE SEPARATE SHEET IF NEEDED)
9. KEEP ALL RECEIPTS FROM GREASE HAULERS

GREASE INTERCEPTORS MUST BE CLEANED WHENEVER 25% OF THE OPERATING DEPTH IS OCCUPIED BY FATS, OILS, GREASE AND SETTLED SOLIDS OR AT A MINIMUM OF ONCE EVERY 3 MONTHS WHICHEVER IS MORE FREQUENT



KEEP THIS FORM IN AN ACCESIBLE PLACE SO THAT IT CAN BE MADE AVAILABLE TO BUREAU PERSONNEL DURING INSPECTIONS OR UPON DEMAND